

Chipper Body Specifications & Features

Long Sill	7" Structural Channel
Cross Member	3" Structural Channel
Cross Member Spacing	12" On - Center
Floor Deck	3/16" Smooth Seamless Plate
Floor Deck	Fully Gusseted to Walls on Sides and Front
Front Wall	11 ga. Sheet, Horizontally Formed Rib Bracing
Side Walls	11 ga. Sheet, Horizontally Formed Rib Bracing
Roof	12 ga. Sheet, Horizontally Formed Rib Bracing
Rear Cross Bar	7 ga. Sheet w/ Integrated Structural Support
Rear Posts	2" Square Tubing x 3/16" Wall Thickness
Rear Doors	Barn Doors, Square Tubing Frame w/ 12 ga. Sheet
Rear Door Hinges	Greasable Door Hinges
Rear Doors Latch	HD Cam Type Latch
Rear Skirt	7 ga. Sheet with Recessed Lighting
Rear Skirt Lights	(4) S/T/T LED & (2) Reverse LED
Rear Roof Lights	S/T/T LED & Reverse LED
Clearance Lights	3/4" LED Federal 108 Spec
Wiring	Modular Plug & Play Harness Connects Directly to the OEM Truck Harness
Paint	Polyurethane Top Coat
Mud Flaps	Standard for Each Rear Wheel
Back Up Alarm	Standard 97 Decibel Alarm

Popular Options	
Receiver Hitch	16,000 lbs. Rated 2" Receiver Tube with Integrated ICC Bumper
Receiver Hitch	21,000 lbs. Rated 2-1/2" Receiver Tube with Integrated ICC Bumper
Pintle Hitch	15 ton Pintle Hitch with 16,000 lbs. Rated 2" Receiver Tube and Integrated ICC Bumper
Pintle Hitch	15 ton Pintle Hitch with 21,000 lbs. Rated 2-1/2" Receiver Tube and Integrated ICC Bumper
Toolbox	Underbody Toolboxes
Toolbox	Cross Over I-Box
Toolbox	Integrated Pole Saw Box on P/S of Body
Front Wall	Integrated Attic Above Cross Over I-Box
Rear Doors	Single Rear Door, Square Tubing Frame w/ 12 ga. Sheet
Paint	Custom Color Polyurethane Top Coat