

### Contractor Dump 100 Series Specifications and Features

Long Sill	6" or 7" Structural Channel
Cross Member	3" or 4" Structural Channel
Cross Member Spacing	12" On - Center
Floor Deck	3/16" Smooth Seamless Plate
Side Rail	Integrated 10 ga. Sheet, Sloped 45 Degrees
Bulkhead	Integrated 11 ga. Sheet
Sides	10 ga Formed Sides with No Vertical Posts
Side Height	12", 18" & 24" Available
Top Rail	3" x 3/16" Structural Tubing
Side Boards	6" Board Brackets
Tail Gate	Fully Boxed 3 Panel Tail Gate
Tail Gate Top Rail	3" x 3/16" Structural Tubing
Tail Gate Lower Hardware	Full Width, One Piece 1" Pin
Tail Gate Upper Hardware	1/2" Plate Offset Upper Hinge Arm
Cab Protector	Integrated 24" Cab Protector with Tarp Provision
Rear Skirt	7 ga. Sheet with Recessed Lighting Under Tail Gate
Rear Skirt Lights	(4) S/T/T LED & (2) Reverse LED
Clearance Lights	3/4" LED Federal 108 Spec
Wiring	Modular Plug & Play Harness Connects Directly to the OEM Truck Harness
Paint	Black Polyurethane Top Coat
Mud Flaps	Standard for Each Rear Wheel
Back Up Alarm	Standard 97 Decibel Alarm

Popular Options	
Sides	Folding Side Rails
Sides	Vertical Side Bracing
Tail Gate Upper Hardware	Drop Pin Upper Hardware for Drop Down Tail Gate
Tail Gate	Metering Door in Tail Gate
Lighting	S/T/T Lights in Rear Posts
Cab Shield	Available from 12" to 36" in 6" Increments
Tarp	Manual Tarp without Side Arms
Tarp	Electric or Manual Tarp with Side Arms
Receiver Hitch	16,000 lbs. Rated 2" Receiver Tube with Integrated ICC Bumper
Receiver Hitch	21,000 lbs. Rated 2-1/2" Receiver Tube with Integrated ICC Bumper
Pintle Hitch	15 ton Pintle Hitch with 16,000 lbs. Rated 2" Receiver Tube and Integrated ICC Bumper
Pintle Hitch	15 ton Pintle Hitch with 21,000 lbs. Rated 2-1/2" Receiver Tube and Integrated ICC Bumper
Toolbox	Underbody Toolboxes
Paint	Custom Color Polyurethane Top Coat