

Flatbed Dump Body Specifications & Features

| | |
|----------------------|--|
| Long Sill | 7" Structural Channel |
| Cross Member | 3" Structural Channel |
| Cross Member Spacing | 12" On - Center |
| Floor Deck | 3/16" Smooth Seamless Plate |
| Side Rail | 3-1/2" x 1/4" Angle Iron |
| Bulkhead | Standards and Window Screen |
| Rear Skirt | 7 ga. Sheet with Recessed Lighting |
| Rear Skirt Lights | (4) S/T/T LED & (2) Reverse LED |
| Clearance Lights | 3/4" LED Federal 108 Spec |
| Bumper | ICC Bumper |
| Stake Pockets | External Pockets for 1-1/2" x 3-1/2" Standards |
| Rub Rail | 3/8" x 2-1/2" on Each Side & Rear |
| Wiring | the OEM Truck Harness |
| Paint | Black Polyurethane Top Coat |
| Mud Flaps | Standard for Each Rear Wheel |
| Back Up Alarm | Standard 97 Decibel Alarm |

| Popular Options | |
|-----------------|---|
| Floor Deck | 3/16" AR400 Smooth Seamless Plate |
| Floor Deck | 1/4" Smooth Seamless Plate |
| Side Rail | 3/8" x 4" Flat Stock |
| Sides | Heavy Duty Sides & Barn Doors |
| Sides | Extreme Duty Sides & Barn Doors |
| Sides | Folding Sides & 4 Pin Tailgate |
| Sides | 42" Stake Panel Sides |
| Sides | Drop In Side Rails |
| Hoist | Scissor Hoist with Electric / Hydraulic Pump |
| Hoist | Scissor Hoist with PTO & Pump |
| Receiver Hitch | 16,000 lbs. Rated 2" Receiver Tube with Integrated ICC Bumper |
| Receiver Hitch | 21,000 lbs. Rated 2-1/2" Receiver Tube with Integrated ICC Bumper |
| Pintle Hitch | 15 ton Pintle Hitch with 16,000 lbs. Rated 2" Receiver Tube and Integrated ICC Bumper |
| Pintle Hitch | 15 ton Pintle Hitch with 21,000 lbs. Rated 2-1/2" Receiver Tube and Integrated ICC Bumper |
| Pintle Hitch | 25 ton Swivel Pintle Hitch with Integrated ICC Bumper |
| Toolbox | Underbody Toolboxes |
| Toolbox | Top Side Toolboxes |
| Toolbox | Back Pack Toolboxes |
| Cargo Control | Underbody Sliding Winch Track |
| Cargo Control | Underbody Strapping Rail |
| Paint | Custom Color Polyurethane Top Coat |