

Flatbed Dump Body Specifications & Features

Long Sill	7" Structural Channel
Cross Member	3" Structural Channel
Cross Member Spacing	12" On - Center
Floor Deck	3/16" Smooth Seamless Plate
Side Rail	3-1/2" x 1/4" Angle Iron
Bulkhead	Standards and Window Screen
Rear Skirt	7 ga. Sheet with Recessed Lighting
Rear Skirt Lights	(4) S/T/T LED & (2) Reverse LED
Clearance Lights	3/4" LED Federal 108 Spec
Bumper	ICC Bumper
Stake Pockets	External Pockets for 1-1/2" x 3-1/2" Standards
Rub Rail	3/8" x 2-1/2" on Each Side & Rear
Wiring	the OEM Truck Harness
Paint	Black Polyurethane Top Coat
Mud Flaps	Standard for Each Rear Wheel
Back Up Alarm	Standard 97 Decibel Alarm

Popular Options	
Floor Deck	3/16" AR400 Smooth Seamless Plate
Floor Deck	1/4" Smooth Seamless Plate
Side Rail	3/8" x 4" Flat Stock
Sides	Heavy Duty Sides & Barn Doors
Sides	Extreme Duty Sides & Barn Doors
Sides	Folding Sides & 4 Pin Tailgate
Sides	42" Stake Panel Sides
Sides	Drop In Side Rails
Hoist	Scissor Hoist with Electric / Hydraulic Pump
Hoist	Scissor Hoist with PTO & Pump
Receiver Hitch	16,000 lbs. Rated 2" Receiver Tube with Integrated ICC Bumper
Receiver Hitch	21,000 lbs. Rated 2-1/2" Receiver Tube with Integrated ICC Bumper
Pintle Hitch	15 ton Pintle Hitch with 16,000 lbs. Rated 2" Receiver Tube and Integrated ICC Bumper
Pintle Hitch	15 ton Pintle Hitch with 21,000 lbs. Rated 2-1/2" Receiver Tube and Integrated ICC Bumper
Pintle Hitch	25 ton Swivel Pintle Hitch with Integrated ICC Bumper
Toolbox	Underbody Toolboxes
Toolbox	Top Side Toolboxes
Toolbox	Back Pack Toolboxes
Cargo Control	Underbody Sliding Winch Track
Cargo Control	Underbody Strapping Rail
Paint	Custom Color Polyurethane Top Coat