

Gooseneck GN Body Specifications & Features

Long Sill	5" Structural Channel
Cross Member	3" Structural Channel
Cross Member Spacing	16" On - Center
Floor Deck	1/8" Treadplate
Horizontal sheet seams over cross member eliminates sheet seperation.	
Side Rail	Integrated 1/8" Treadplate
Bulkhead	Integrated 3" x 2" x 11 ga. Tubing Perimeter with 11 ga. Sheet and Window Screen
Bulkhead Lights	(2) S/T/T LED & (2) Reverse LED
Rear Skirt	Box
Rear Skirt Lights	(4) S/T/T LED & (2) Reverse LED
Clearance Lights	3/4" LED Federal 108 Spec
Receiver Hitch	16,000 lbs. Rated 2" Receiver Tube with Integrated ICC Bumper
GN Hitch	30,000 lbs. Rated 2-5/16" Ball with Double Hinged Access Door
Trailer Plugs	(2) 7W RV
Stake Pockets	External Pockets for 1-1/2" x 3-1/2" Standards
Rub Rail	3/8" x 2-1/2" on Each Side
Wiring	Modular Plug & Play Harness Connects Directly to the OEM Truck Harness
Paint	Black Polyurethane Top Coat
Mud Flaps	Standard for Each Rear Wheel
Back Up Alarm	Standard 97 Decibel Alarm

Popular Options	
Floor Deck	10 ga. Smooth Deck
Receiver Hitch	21,000 lbs. Rated 2-1/2" Receiver Tube with Integrated ICC Bumper
GN Hitch	30,000 lbs. Rated B&W Style Turn Over Hitch with 2-5/16" Ball
GN Hitch	30,000 lbs. Rated 3" Ball with Double Hinged Access Door
GN Hitch	Add 5th Wheel Rails to Bed Floor
GN Hitch	GN Hitch Trough
GN Hitch	Delete GN Hitch
Sides	Drop In Side Rails
Sides	Folding Side Rails
Toolbox	Underbody Toolboxes
Toolbox	Top Side Toolboxes
Lighting	Deck Light Between Light Boxes
Paint	Custom Color Polyurethane Top Coat