

Ramp Body Specifications & Features

Long Sill	5" Structural Channel
Cross Member	3" Structural Channel
Cross Member Spacing	12" On - Center
Floor Deck	3/16" Treadplate
Horizontal sheet seams over cross member eliminates sheet separation.	
Side Rail	3-1/2" x 1/4" Angle Iron
Bulkhead	Integrated 11 ga. Sheet with 3" Structural Channel Standards and Window Screen
Dovetail	5' Dovetail with HD 4 lb. Grating Floor, Open Floor Design Gives Full Width Traction on Dovetail
Dovetail	(2) 8,000 lb. Drop Leg Outriggers on Dovetail
Rear Header	1/4" Formed Channel with Integrated Lighting
Ramps	7' Ladder Style Equipment Ramps with Spring Assist, 10,000 lb. Loading Capacity
Rear Lights	(4) S/T/T LED & (2) Reverse LED
Clearance Lights	3/4" LED Federal 108 Spec
Cargo Control	(6) 3/4" D-Ring Tie Downs
Safety	(2) Stirrup Steps on Dovetail
Stake Pockets	External Pockets for 1-1/2" x 3-1/2" Standards
Rub Rail	3/8" x 2-1/2" on Each Side
Wiring	Modular Plug & Play Harness Connects Directly to the OEM Truck Harness
Paint	Black Polyurethane Top Coat
Mud Flaps	Standard for Each Rear Wheel
Back Up Alarm	Standard 97 Decibel Alarm

Popular Options	
Receiver Hitch	10,000 lbs. Rated 2" Receiver Tube
Cargo Control	Underbody Sliding Winch Track
Cargo Control	Additional 3/4" D-Ring Tie Downs
Sides	Drop In Side Rails
Sides	Folding Expanded Metal Side Rails
Toolbox	Underbody Toolboxes
Toolbox	Underbody Gas Can Box
Toolbox	Top Side Toolboxes
Toolbox	Landscaping Style Front Toolbox & Bulkhead
Accessories	Handtool Storage on Bulkhead
Accessories	Auxillary Fuel Tank & Pump
Paint	Custom Color Polyurethane Top Coat