

Van Body Specifications & Features

Long Sill	4" I-Beam
Cross Member	3" I-Beam
Cross Member Spacing	15" On - Center
Floor	1-1/8" Laminated Hardwood
Roof	One Piece .032 Aluminum
Roof Bow Spacing	24" On - Center
Rear Door	Non-Insulated Roll Up Door, Wood Slats
Rear Frame	10 Gauge Galvanealed, Painted White
Sides	.040 Prepainted White Aluminum
Side Post	Formed "Z" Post
Side Post Spacing	16" On - Center
Full Height Lining	3/8" Plywood (Side Walls) 1/2" Plywood (Front Wall)
Dome Light	LED Dome Light
Grab Handles	Grab Handle on Each Rear Post
Lights	LED Federal 108 Spec
Bumper	ICC Bumper

Popular Options	
Access	Side Door
Access	Dovetail & Ramps
Liftgate	Tuck-Under Liftgate
Liftgate	Rail Style Liftgate
Liftgate	Cantilever Liftgate
Receiver Hitch	16,000 lbs. Rated 2" Receiver Tube with Integrated ICC Bumper
Receiver Hitch	21,000 lbs. Rated 2-1/2" Receiver Tube with Integrated ICC Bumper
Toolbox	Underbody Toolboxes